

AS21002 - 5AEF579E-3EB3-4FB6-86B8-9AF294A0DF24.jpeg



AS21002 - D9F51CD2-9B79-4429-84A4-CED5F50B1A97.jpeg



AS21002 - 70D7AEBE-3635-4309-B0DC-775E3756EBE1.jpeg



AS21002 - D7E29DE3-2D9D-4991-BED5-68102A036DE5.jpeg







ENTRAPPED













MANUFACTURED BY / FABRIQUE PAR: **FOREST RIVER, Inc** DATE: **6/30/2010** THIS VEHICLE CO  
 U.S. FEDERAL MO  
 STANDARDS IN EF  
 MANUFACTURE SH  
 VIN/NTV: **4X4TVCB28BK400212** TYPE/TYPE: **TRA/REM** TRA/REM  
 GVWR/PNBV: **3457 KG ( 7622 LB)** VCT26VBH  
 Coupler Size: **VCK400212**

	CAWR/PNEU	TIRE/S/PNEU	RIMS/IANTE	COLD INFL PRESS/ P/SS DE CONF/ A FROID
FRONT/ AVANT	1588 KG 3500 LB)	ST205/75D14/C	14X5.5JJ	345 KP SINGLE DUAL 50 PSI/LP <input checked="" type="checkbox"/>
INTERM/ INTERM	0 KG 0 LB)			0 KP SINGLE DUAL 0 PSI/LP <input type="checkbox"/>
REAR/ ARRIERE	1588 KG 3500 LB)	ST205/75D14/C	14X5.5JJ	345 KP SINGLE DUAL 50 PSI/LP <input checked="" type="checkbox"/>

THIS VEHICLE CONF  
 STANDARDS PRESCA  
 MOTOR VEHICLE SAF  
 EFFECT ON THE DATE  
 CE VEHICL EST CONFO  
 NORMIES QUI UI SONT AF  
 DU REGLEMENT SUR LA S  
 AUTOMOBILES DU CANADA  
 DATE DE SA FABRICATION.



**TIRE AND LOADING INFORMATION**

The combined weight of Cargo should Never Exceed:  
 1143 Kgs or 2520 Lbs

TIRE	SIZE	COLD TIRE PRESSURE	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT	ST205/75D14/C	50 PSI/345 KPA	
REAR	ST205/75D14/C	50 PSI/345 KPA	
SPARE	ST205/75D14/C	50 PSI/345 KPA	



**RENSEIGNEMENTS SUR LES PNEUS**

Le poids du chargement ne doit ja  
 1143 Kgs or 2520 Lbs

PNEU	DIMENSIONS	PRESSION DES PNEUS À
AVANT	ST205/75D14/C	50 lb/ps2 345 KP
ARRÈRE	ST205/75D14/C	50 lb/ps2 345 KPA
DE SECOURS	ST205/75D14/C	50 lb/ps2 345 KPA

RECREATIONAL VEHICLE TRAILER CARGO CARRYING CAPACITY  
 Dry Weight: 5000 VIN: 4X4TVCB28BK400212  
 THE WEIGHT OF CARGO SHOULD NOT EXCEED  
 1143 Kg or 2520 lbs  
 CAUTION:



































